



pepsi

High Visibility Vendors (HVV & HV3) Vending Line



HVV



HV3

Pop Over for Some Pop!

The HVV is designed to attract attention in high volume locations, whereas the High Value Visibility Vendor (HV3) is a low cost, energy efficient alternative to the Pepsi HVV.

Standard features include LED lights, a curved signface, sleek selection buttons, DBV panel, and T-Handle lock assembly.

The rugged top retainer ensures consistent product alignment every time the door is closed. Slide out loading rack allows for greater access to the columns for 2 handed product loading.

PEPSI, PEPSI-COLA, and THE PEPSI BIG BOLD BLUE design are registered trademarks of PepsiCo, Inc.



Model	621 HV3	721 HV3	821 HV3	621 HVV	721 HVV	821 HVV
Total Can Capacity	544	680	800	544	680	800
Total PET Bottle Capacity	240	300	360	240	300	360
Selection Spaces/Columns	6/8	10/10	10/10	6/8	12/10	12/10
Dimensions* (H x W x D)	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Shipping Weight*	570 lbs	660 lbs	725 lbs	570 lbs	660 lbs	725 lbs
Operation Voltage	115v 60Hz					
Amp Rating	8					
Energy Consumption	≤3.0 kWh/ day	≤3.1 kWh/ day	≤3.5 kWh/ day	≤3.8 kWh/ day	≤3.9 kWh/ day	≤4.3 kWh/ day
Lighting	LED					
Refrigerant	R-134a or R-240			R-134a, R-744 or R-240		
Lock Type	T-Handle			E-Lock		
Capacity per Column	12 oz Can	68	80	68	80	
	20 oz PET Bottle**	30	36	30	36	

*Dimensions and shipping weight will vary slightly.

**Product capacities will vary based on the shape and size of the bottle.

- Rugged top retainer ensures consistent product alignment every time the door is closed.
- The V21 stack allows for maximum flexibility during product loading. Most products can be loaded caps to back, butt-to-butt, or in combination.
- The V21 has a full function MDB controller with DEX/UCS, recycler and wireless telemetry compatibility.
- Energy management features included on every model make the V21 one of the most energy efficient machines available: real time clock, lighting and refrigeration controls, cyclopentane injected foam insulation (HFC free) and now the option of alternative natural refrigerants.
- The V21 utilizes 24 volt, DC motors that are installed with only two screws for easy servicing. There are no micro switches or timing cams.
- Slide out loading rack allows for greater access to the columns for 2 handed product loading.
- The time tested V21 product delivery system design ensures reliable vending due to reduced sensitivity to package diameter and shape.
- The V21's epoxy coated vend chute provides smooth product delivery.



SandenVendo America, Inc
www.vendoco.com
+1 800 344 7216

At SandenVendo America, we take our commitment to the environment very seriously. That's why we're proud to offer our full range of vending machines charged with R290 HC. All models are cUL listed and meet or exceed DOE and Energy Star requirements. R290 is a safe and abundant natural refrigerant with a zero Ozone Depleting Potential and a Global Warming Potential (GWP) of 3, compared to HFC - R134a's GWP of 1,300, so it's clear that R290 is the sustainable choice of the future.